

Hidden Corners of Regina

2022 International Rexx Symposium Virtual

Mark Hessling
12/13 September 2022



Hidden Corners of Regina

- Invoking Regina: rexx vs regina
- Constant Variables
- BIFs
- Queues
- Address...With
- Callbacks
- Generic Call Interface (GCI)



Hidden Corners of Regina

- Language Support for error messages
- Static dynamic loading
- Zsh module



rexx vs regina

- rexx executable
 - no support for external function packages
 - Slightly faster
- regina executable
 - Supports external function packages
 - Slightly slower



Constant Variables

- Platform-specific constants:
 - .LINE – line number in Rexx program
 - .FILE – file name of running Rexx program
 - .ENDOFLINE – end of line sequence; *LF*, *CRLF*
 - .DIRSEP – directory separator; / or \



BIFs

- Some Regina specific builtin functions:
 - PoolId()
 - GetCaller()
 - GetCallStack()
 - RxFuncErrMsg()



Queues

- Queue Names
- External Queues
 - Queues managed by an external process
- Internal Queues
 - Queues managed by the running process
- rxstack, rxqueue and rxqueue()



Queue Names

- Syntax:
 - [queue][@machine[:port]]
- queue – can be blank
- machine – the IP address of server running rxstack; default 127.0.0.1
- port – TCP/IP port that rxstack listens on; default 5757



External Queues

- Managed by external process: rxstack
- Communication between processes over TCP/IP
- Communication between machines
- Slower, but should not be that slow!
- Requires rxstack process running



Internal Queues

- Internal to Regina process
- Faster
- Does not require rxstack process running
- `OPTION INTERNAL_QUEUES` overrides queue name rules



rxstack

- By default listens for a connection from the local host on port 5757
- Change listening port
 - -p, --port port
- Allow world access – be careful!
 - -w, --world



rxqueue

- Works as a filter; input from stdin
- Switches:
 - -D, --debug
 - -t, --text "text to place on queue" → instead of stdin
- Actions:
 - /delete – delete the queue
 - /queued – return number of lines on queue
 - /pull – pull lines from queue and display on stdout
 - /list – display list of queues held by rxstack
 - /clear – remove all lines in queue



rxqueue()

- Timeout (T) option
 - Wait specified number of milliseconds for something to appear on the queue
 - Specify 0 to wait forever



Address...With

- FIFO and LIFO extensions to INPUT and OUTPUT
- NOEOL extension to INPUT



Callbacks

- Enable Rexx code to be executed on an event
- Requires RexxCallback() API
- Several external function packages require this
 - Rexx/CSV
 - Rexx/CURL
 - Rexx/DW
 - Rexx/WPi



Generic Call Interface (GCI)

- Enables any entry point in any DLL/shared library to be treated as a Rexx function
- Treat as experimental



Language Support

- Error messages in specified language
 - .de, en, es, no, pl, pt, sv, tr
 - REGINA_LANG environment variable
 - REGINA_LANG_DIR to specify location



Static Dynamic Loading

- Dynamic Loading
 - External function packages usually loaded from DLL/shared library at runtime
 - Not supported on some platforms; DOS, QNX
 - Load via RxFuncAdd()
- Static Dynamic Loading
 - Loaded at build time and statically linked
 - Load via RxFuncAdd()
 - Available on all platforms



Zsh module

- Unix/Linux shell zsh module
- Build zsh from source with Regina module
- Allows shell environment; current working directory and environment variables to be set by Regina program and "stick"
- Invoked by zsh "builtin" command; zregina



Questions

